

ENERGY AT FAIR PRICE



Simple professional generator. Pramac has designed this generator to ensure a high performance level at attractive price. Powerful and strong generator; easy to maintain, it will be soon essential to all your activities.

**Standard Equipment**Starting system Recoil**Main Features**

Frequency	Hz	50
Voltage	V	230
Power factor	cos $\phi$	0.9
Phase and connection		1

**Power Rating**

Standby power LTP	kVA	5.1
Standby power LTP	kW	4.6
Continuous power COP	kVA	4.2
Continuous power COP	kW	3.9

**Ratings definition (According to standard ISO8528 1:2005)****COP** - Continuous Power:

It is defined as being the maximum power which a generating set is capable of delivering continuously for an unlimited number of hours, with the maintenance intervals and procedures being carried out as prescribed by the manufacturers.

**LTP** - Limited-Time running Power:

It is defined as the maximum power available, under the agreed operating conditions, for which the generating set is capable of delivering for up to 500 h of operation per year (whose no more than 300 for continuative use) with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. No overload capability is available.

**Engine Specifications**

Brand	Honda	
Model	GX270 Recoil	
Engine cooling system	Air	
Displacement	cm <sup>3</sup>	270
Aspiration	Natural	
Speed governor	Mechanical	
Operating Speed-Nominal	rpm	3000
Oil capacity	L	1.1
Fuel	Gasoline	
Starting system	Recoil	
Fuel consumption @ 75% PRP	L/h	1.67


**Alternator Specifications**

Class	H	
IP protection	23	
Poles	2	
Voltage tolerance	%	+5, - 10 (cosφ1)

**Dimensional data**

Length	mm	715
Width	mm	540
Height	mm	490
Dry weight	kg	61
Fuel tank capacity	L	5.3

**Autonomy**

Running time @ 75% PRP	h	3.17
------------------------	---	------

**Noise level**

Guaranteed noise level (LWA)	db(A)	97
Noise pressure level @ 7 mt	db(A)	69

## GENSET CONTROL

### COMMANDS:

- Selector switch: OFF - ON
- Starting systems: Recoil
- Fuel Cock

### PROTECTIONS STANDARD:

- Thermal protection
- Oil Guard

### SOCKET TYPE

SCHUKO 230V 16A

2



## SUPPLEMENTS CONTROL (Available when ordered)

### ASCODIF

Extra Protection with:

- differential protection 30mA
- circuit breaker – hourmeter



### ACCESSORIES

#### TRANSPORTATION KIT

- With fix handles
- With folding handles



#### LIGHT TOWER

for portable generators (with tubular frames)

- Maximum Height 4.2m
- Elevations Pneumatic
- Quick open/close systems for legs
- Mast support and four lifting
- Lamp available Watt/Type:
  - n.4 X 500W Halogen (required power from generator: 2.5kVA 230V Single Phase)
  - n.4 X 1000W Halogen (required power from generator: 5,0kVA 230V Single Phase)



#### MTS- MANUAL TRANSFER SWITCH

- Manual transfer switch 40A (for manual control versions 230V)



Publishing date: 03/12/13

©2012 | PR INDUSTRIAL s.r.l. | All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice | ENERGY GENERATION is registered trademarks of PR INDUSTRIAL s.r.l. Other company, product or service names may be trademarks or service marks of others. RevA (06/2012).